

and FINISHING PHASES


phase 4	phase 5
SECTION AFTER FIRST PAINTING STAGE MADE BY ANAPHORESIS	SECTION AFTER SECOND PAINTING STAGE



Uff. Pub. Fondital - CTC 04 P 207 - 01 Novembre 2011 (11/2011)

9PCR04P207

Die cast aluminium radiators for high pressure heating systems




GB

BRAND NAME
NOVA FLORIDA

FONDITAL S.p.A.
25079 VOBARNO (Brescia) Italy
Via Cerreto, 40 - Tel. +39 0365 878.31 - Fax +39 0365 878.576
e mail: fondital@fondital.it - www.novaflorida.it

COMPANY WITH QUALITY MANAGEMENT
SYSTEM CERTIFIED BY DNV
= ISO 9001:2008 =

The manufacturer reserves the right to make any modifications deemed necessary without prior notification.



PAINTING

phase 1	phase 2	phase 3
UNMACHINED SECTION	MACHINED SECTION	WASHING AND CHEMICAL TREATMENT OF THE SURFACES




* This picture shows the various phases of processing and painting of radiators.
It may not represent the model described in the present document.

EVOLUTION: SERIR S5

Serir S5 is NOVA FLORIDA's new range of high-tech radiators that feature numerous technological innovations:


- Innovative geometry of the 5 rows of side fins, developed with thermo-fluid dynamic simulations and climatic chamber tests, resulting in a high heat output with a smaller surface area and hence less weight.
- Presence of rear openings allowing enhanced heat exchange by convection.
- A new cap for the element.
- Ornamental patent, and patent pending for new technical developments.

	Depth (C) mm	Height (B) mm	Centre distance (A) mm	Length (D) mm	Connection diameters inches	Water capacity litres/sect.	Weight Kg/sect.	Exponent n	Coefficient K _m	Heat output ΔT 30K W/sect.	Heat output ΔT 50K W/sect.
500/100	97	557	500	80	G1	0.31	1.30	1.3014	0.7191	60.1	116.9



Maximum working pressure: 1600 kPa (16 bar)

Characteristic equation of the model $\Phi = K_m \Delta T^n$ (reference EN 442-1). The thermal efficiency values, expressed at ΔT 50K, comply with EN 442-2 and are certified by the MRT Lab of the Milan Polytechnic, notified body no. 1695.



- The new cap is not welded and hydraulic seal is provided by an **O-ring seal**.
- The new cap is made of **aluminized steel**.
- **No welds, so no problems with burrs** at the bottom of the radiator.
- **All the caps** for the models in the Serir S5 range **undergo Aleternum® anticorrosion treatment**.

2011 BRAND NEW CREATION

- S5 is **lighter** than the models in the S3 range, and hence easier to transport and install;
- S5 has an **optimal weight-to-heat output ratio**;
- S5 features numerous **exclusive technological innovations**;
- S5 has an **innovative cap**.



Openings on the rear side

- new configuration of side fins for **higher heat output**
- new technical solution: **cap with no welding required**



SERIR S5



Fondital guarantees **Serir S5** for **10 years** from the date of installation against all production defects providing the heating system is conform to the regulations, in compliance with the standards in force and provided the instructions on installation, use and correct maintenance supplied with the product have been observed.