PRICE LIST JULY 2015



Die-cast aluminium radiators and accessories The prices include: painting, assembling and packaging (accessories must be ordered separately) Standard assembly: from 3 to 14 sections Standard colour: white RAL 9010

Model	Code	Width mm	Height mm	Centre distance mm	Length mm	Diameter of fitting inches	Water capacity litres/sect.	Weight Kg/sect.	Heat output $\Delta T 50K$ W/sect.	Heat output ΔT 30K W/sect.	Exponent n	Coefficient K _m	Price per section €
500/100	V355034	97	557	500	80	G1	0.31	1.30	116.9	60.1	1.3014	0.7191	14.40

Maximum working pressure: 1600 kPa (16 bar).

Characteristic equation of the model: $\Phi = Km \cdot \Delta T^n$ (reference EN 442-1). The stated thermal power values comply with the European standard EN 442-2 and have been certified by the Milan Polytechnical Institute, M.R.T. Laboratory - Notified body n. 1695.

Accessories (to be ordered separately)

	Code				€		Code			€
A 1/1	520201 520202	RH		1"G automatic air-purging valve, chromed (always to be installed with the vent in upward position)	6.50	A 18	550035 RH 550036 LH	- ~11	Bracket to be screwed on to the wall	0.53
A 2/1	510011			1"G joining nipple	0.26	A 20	550037	BAR	Installation kit with two adjustable, coated brackets	5.6
A 4/1	525014 525114	RH LH		1"G zinc-plated, paint-coated plug	1.10					
A 6/1	526014	RH		Reducer 3/8 white	-	A 26/1	550090		Nipple wrench 1"G	20.3
	526214	RH		Reducer 1/2 white			560257	02-00	Plastic key	5.0
	526414	RH		Reducer 3/4 white		A 40/2				
	526114	LH		Reducer 3/8 white	1.00	A 80			Mounting kit for radiators each containing: - 2 zinc-plated, paint-coated reducers 1/2"G, Rh - 2 zinc-plated, paint-coated reducers 1/2"G, Lh - 4 retaining gaskets - 1 manual air-purging valve 1/2"G with gasket - 1 (1/2"G) plug with gasket	
	526314	LH		Reducer 1/2 white	-		550103			
	526514	LH		Reducer 3/4 white						
A 8/1	525214	RH		Valve plug 1/4 white						7.9
	525414	RH		Valve plug 1/8 white	1.00					
	525314	LH		Valve plug 1/4 white	1.00					
	525514	LH		Valve plug 1/8 white						<u> </u>
A 10/1	530105		Nipple gasket (asbestos-free)		0.08				Mounting kit for radiators each containing: - 2 zinc-plated, paint-coated reducers 1/2"G, Rh - 2 zinc-plated, paint-coated reducers 1/2"G, Lh - 4 retaining gaskets - 1 manual air-purging valve 1/2"G with gasket - 1 (1/2"G) plug with gasket - 3 brackets to be screwed on to the wall	
A 11/1	530108 540024 550020		\bigcirc	Gasket for plugs (asbestos-free)	0.11	A 81	550104			12.3
A 13				Touch-up spray paint (white RAL 9010) cc 400	5.80					
A 16				Bracket to be embedded in the wall mm 175	0.40					



FONDITAL S.p.A.

Via Cerreto, 40 - 25079 VOBARNO (Brescia) Italy Tel.: +39 0365 878.31 - Fax: +39 0365 878.304 E-mail: info@fondital.it - Web: www.novaflorida.com COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV GL = |SO 9001 =

CE₁₁