

# PRICE LIST JULY 2016



## Die-cast aluminium radiators and accessories

The prices include: painting, assembling and packaging (accessories must be ordered separately)

Standard assembly: from 3 to 14 sections for model 500.

Standard colour: white RAL 9010



| Model      | Code    | Width | Height | Centre distance | Length | Diameter of fitting | Water capacity | Heat output $\Delta T$ 50K | Heat output $\Delta T$ 30K | Exponent | Coefficient | Price per sect. |
|------------|---------|-------|--------|-----------------|--------|---------------------|----------------|----------------------------|----------------------------|----------|-------------|-----------------|
|            |         | mm    | mm     | mm              | mm     | inches              | litres/sect.   | W/sect.                    | W/sect.                    | n        | $K_m$       | €               |
| B4 350/100 | V689014 | 97    | 407    | 350             | 80     | G1                  | 0.21           | 91.5                       | 47.3                       | 1.2910   | 0.5865      | 14.00           |
| B4 500/100 | V689034 | 97    | 557    | 500             | 80     | G1                  | 0.25           | 124.6                      | 64.4                       | 1.2917   | 0.7957      | 15.16           |
| B4 600/100 | V689044 | 97    | 657    | 600             | 80     | G1                  | 0.30           | 143.6                      | 74.3                       | 1.2902   | 0.9230      | 16.44           |
| B4 700/100 | V689054 | 97    | 757    | 700             | 80     | G1                  | 0.36           | 161.7                      | 82.9                       | 1.3064   | 0.9752      | 19.48           |
| B4 800/100 | V689064 | 97    | 857    | 800             | 80     | G1                  | 0.39           | 178.7                      | 91.9                       | 1.3022   | 1.0956      | 20.53           |

Maximum working pressure: 1600 kPa (16 bar)

Characteristic equation of the model  $\Phi = K_m \Delta T^n$  (reference EN 442-1). The thermal efficiency values, expressed at  $\Delta T$  50K, comply with EN 442-2.

The new cap, joined via a thermo-electrical process

## Accessories (to be ordered separately)

|        | Code   |    | €    |
|--------|--------|----|------|
| A 1/1  | 520201 | RH | 6.50 |
|        | 520202 | LH |      |
| A 2/1  | 510011 |    | 0.26 |
| A 4/1  | 525014 | RH | 1.10 |
|        | 525114 | LH |      |
| A 6/1  | 526014 | RH | 1.00 |
|        | 526214 | RH |      |
|        | 526414 | RH |      |
|        | 526114 | LH |      |
|        | 526314 | LH |      |
|        | 526514 | LH |      |
| A 8/1  | 525214 | RH | 1.00 |
|        | 525414 | RH |      |
|        | 525314 | LH |      |
|        | 525514 | LH |      |
| A 10/1 | 530105 |    | 0.08 |
| A 11/1 | 530108 |    | 0.11 |
| A 13   | 540024 |    | 5.80 |
| A 16   | 550020 |    | 0.40 |

|        | Code   |    | €     |
|--------|--------|----|-------|
| A 18   | 550035 | RH | 0.53  |
|        | 550036 | LH |       |
| A 20   | 550037 |    | 5.60  |
| A 26/1 | 550090 |    | 20.30 |
| A 40/2 | 560257 |    | 5.00  |
| A 80   | 550103 |    | 7.90  |
| A 81   | 550104 |    | 12.30 |