


Die-cast aluminium radiators and accessories**The prices include:** painting, assembling and packaging (accessories must be ordered separately)**Standard assembly:** from 3 to 14 sections for model 500.**Standard colour:** white RAL 9010**The new cap, joined via a thermo-electrical process**

Model DESIDERYO	Code	Width	Height	Centre distance	Length	Diameter of fitting	Water capacity	Heat output ΔT 30K	Heat output ΔT 50K	Exponent	Coefficient	Price per sect.
		mm	mm	mm	mm	inches	litres/sect.	W/sect.	W/sect.	n	K_m	€
B4 350/100	V682014	97	407	350	80	G1	0.21	47.3	91.5	1.2910	0.5865	14.00
B3 500/100	V664034	97	557	500	80	G1	0.25	59.6	115.2	1.2896	0.7422	14.00
B3 600/100	V664044	97	657	600	80	G1	0.28	68.5	133.4	1.3046	0.8101	14.70
B3 700/100*	V664054	97	757	700	80	G1	0.39	75.1	146.0	1.3025	0.8944	18.17
B3 800/100	V664064	97	857	800	80	G1	0.43	85.2	166.0	1.3070	0.9992	18.74

Maximum working pressure: 1600 kPa (16 bar)Characteristic equation of the model $\Phi = K_m \Delta T^n$ (reference EN 442-1). The thermal efficiency values, expressed at ΔT 50K, comply with EN 442-2.

* Provisional data, certification pending.

Accessories (to be ordered separately)

	Code			€
A 1/1	520201	RH		1" G automatic air-purging valve, chromed (always to be installed with the vent in upward position)
	520202	LH		
A 2/1	510011			0.26
A 4/1	525014	RH		1" G zinc-plated, paint-coated plug
	525114	LH		
A 6/1	526014	RH		Reducer 3/8 white
	526214	RH		Reducer 1/2 white
	526414	RH		Reducer 3/4 white
	526114	LH		Reducer 3/8 white
	526314	LH		Reducer 1/2 white
A 8/1	526514	LH	Reducer 3/4 white	1.00
	525214	RH		Valve plug 1/4 white
	525414	RH		Valve plug 1/8 white
	525314	LH		Valve plug 1/4 white
525514	LH	Valve plug 1/8 white		
A 10/1	530105			0.08
A 11/1	530108			0.11
A 13	540024			5.80
A 16	550020			0.40

	Code			€
A 18	550035	RH		Bracket to be screwed on to the wall
	550036	LH		
A 20	550037			5.60
A 26/1	550090			20.30
A 40/2	560257			5.00
A 80	550103			7.90
A 81	550104			12.30