

Die-cast aluminium radiators and accessories
The prices include: painting, assembling and packaging (accessories must be ordered separately)

Standard assembly: from 3 to 14 sections for model 500.

Standard colour: white RAL 9010











Model	Code	Width	Height	Centre distance	Length	Diameter of fitting	Water capacity	Heat output ΔT 50K	Heat output ΔT 30K	Exponent	Coefficient	Price per sect.
		mm	mm	mm	mm	inches	litres/sect.	W/sect.	W/sect.	n	K_m	€
B4 350/100	V685014	97	407	350	80	G1	0.20	89.9	47.2	1.2598	0.6506	14.00
B4 500/100*	V685034	97	558	500	80	G1	0.25	123.8	64.1	1.2890	0.7991	15.16
B4 600/100	V685044	97	658	600	80	G1	0.31	143.6	74.0	1.2981	0.8950	16.44
B4 700/100*	V685054	97	758	700	80	G1	0.36	161.3	83.1	1.2998	0.9986	19.48
B4 800/100	V685064	97	858	800	80	G1	0.39	177.7	91.1	1.3085	1.0635	20.53

Maximum working pressure: 1600 kPa (16 bar)







 Characteristic equation of the model $\Phi = K_m \Delta T^n$ (reference EN 442-1). The thermal efficiency values, expressed at ΔT 50K, comply with EN 442-2.

* Provisional data, certification pending.

Accessories (to be ordered separately)

	Code			€	
A 1/1	520201	RH		1" G automatic air-purging valve, chromed (always to be installed with the vent in upward position)	6.50
	520202	LH			
A 2/1	510011			1" G joining nipple	0.26
A 4/1	525014	RH		1" G zinc-plated, paint-coated plug	1.10
	525114	LH			
A 6/1	526014	RH		Reducer 3/8 white	1.00
	526214	RH		Reducer 1/2 white	
	526414	RH		Reducer 3/4 white	
	526114	LH		Reducer 3/8 white	
	526314	LH		Reducer 1/2 white	
A 8/1	525214	RH		Valve plug 1/4 white	1.00
	525414	RH		Valve plug 1/8 white	
	525314	LH		Valve plug 1/4 white	
	525514	LH		Valve plug 1/8 white	
A 10/1	530105			Nipple gasket (asbestos-free)	0.08
A 11/1	530108			Gasket for plugs (asbestos-free)	0.11
A 13	540024			Touch-up spray paint (white RAL 9010) cc 400	5.80
A 16	550020			Bracket to be embedded in the wall mm 175	0.40

The new cap, joined via a thermo-electrical process

	Code			€	
A 18	550035	RH		Bracket to be screwed on to the wall	0.53
	550036	LH			
A 20	550037			Installation kit with two adjustable, coated brackets	5.60
A 26/1	550090			Nipple wrench 1" G	20.30
A 40/2	560257			Plastic key	5.00
A 80	550103			Mounting kit for radiators each containing: - 2 zinc-plated, paint-coated reducers 1/2" G, Rh - 2 zinc-plated, paint-coated reducers 1/2" G, Lh - 4 retaining gaskets - 1 manual air-purging valve 1/2" G with gasket - 1 (1/2" G) plug with gasket	7.90
A 81	550104			Mounting kit for radiators each containing: - 2 zinc-plated, paint-coated reducers 1/2" G, Rh - 2 zinc-plated, paint-coated reducers 1/2" G, Lh - 4 retaining gaskets - 1 manual air-purging valve 1/2" G with gasket - 1 (1/2" G) plug with gasket - 3 brackets to be screwed on to the wall	12.30